



Frontal dishwashers

DISHWASHER, FI-30B BT

1210305118

Dimensions and Weights

Length	mm	600,00
Depth	mm	600,00
Height	mm	820,00
Net Weight	Kg	54,00
Gross Weight	Kg	61,00
Volume packed	m3	0,39

Electricity

Electric Power	KW	2,82
Voltage 230V - I+N	2x2,5+T - 20 A	
Voltage 230V - III	3x2,5+T - 20 A	
Voltage 400V - III+N	4x2,5+T - 20 A	

Gas

No

DISHWASHER, FI-30B BT

Made of stainless steel.
 Hourly production: 320 dishes/h.
 Maximum diameter of dishes: Ø 32 cm.
 Wash cycle: 0-240".
 Rotating wash and rinse.
 Heated by means of shielded elements.
 Built-in rinse water boiler.
 Tank with 2.8 kW heating element.
 Tank capacity: 25 litres.
 Boiler with 2.2 KW heating element.
 Water consumption: 2.7 litres/rinse.
 Automatic detergent and rinse dispensers.
 Thermostatically adjusted. (wash temperature: 60 °C).
 Safety thermostat.
 Drain pump and drainage cycle.
 Air gap.
 Water inlet hose and drainage hose.
 Safety switch for door opening.
 Adjustable legs.
 Baskets equipment: 1 x CT-10, 1 x CP-16/18 and 1 cutlery containers.
 Power: 2.82 kW.
 Electrical connection cable 1 meter long, outside machine.
 Dimensions: 600 x 600 x 810 mm.

Water

Consumption (lit/h)	41,00
Pressure (Kg/cm2)	2 - 4

Installation	X	Y	Z	Diameters
ELECTRICITY	210	50	65	
DESC.COLD WATER	305	50	65	3/4"
DRAIN	370	50	65	30x25

