



COMMERCIAL & INDUSTRIAL DISHWASHERS

DIRECT

Make & Model	Kromo Lux 60 EL Plus Integral water softener	
Machine dimension (mm) W x D x H	600 x 610 x 850	
Basket size (mm)	500 x 500	
Maximum wash height (mm)	350	
Wash cycles	1,2,3 & 5 minutes (programmable)	
Maximum number of (10") plates per hour (hot fill)	1080	
Maximum power requirements	32 amps single phase	
Supplied with	Fill & Drain hose. 1 Plate & 1 Cup basket. 1 Cutlery holder	√
Integral detergent and rinse aid pumps	Precise dosing for streak free results without waste	√
Drain pump	Allows installation below a worktop and where drains are not at ground level.	√
Class "AA" air gap	Provides category 5 water protection & prevents the possibility of contaminated wash water entering the drinking water supply	√ WRAS approved
Break tank and rinse boost pump	Allows connection to any water supply regardless of water pressure	√
Full wash tank filters	Prevents debris getting into the wash tank keeping the wash water cleaner for longer.	√
Moulded wash tank	No sharp corners for dirt to collect and ensures complete draining	√
One piece wash arms	No jets to remove	√
Separate wash and rinse arms	Ensure 100% wash and rinse coverage for improved results.	√
Double skinned	Keeps radiated heat and noise levels to a minimum and reduces energy loss.	√
Self cleaning cycle	Makes cleaning the machine down at the end of the day easier and quicker	√
Energy saving on stand by	Saves significant amounts of power during standby periods	√
Automatic drain down	No need to remove a drain plug or stand holding a button to drain the machine.	√
Rinse temperature interlock	Guarantees optimised rinsing at a constant 82°C	√
13, 20 or 30 amp connection	Flexible electrical connection options	
Integral water softener	Ensures optimum water quality to deliver a sparkling finish. Saves space over an external water softener.	√
100% fresh water every wash	Can be used to wash glasses and dishes without the need to drain and clean the machine.	